


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

DATA OF LAMP		PHOTOMETRIC DATA Eff: 88.47 lm/W			
MODEL NJZ-FEL-G-20-V01-RZ-F		Imax(cd)	652.7	S/MH(C0/180)	1.21
NOMINAL POWER(W)	20	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	220	TOTAL FLUX(lm)	1804.5	η UP,DN(C0-180)	0.0,49.5
NOMINAL FLUX(lm)	1804.51	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,50.5
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	220	η down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:23 December 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	640.4	635.8	637.0	634.5	638.1	635.7	639.1	637.3	0- 10	61.39	61.39	3.4,3.4
20	600.6	595.1	596.5	592.6	596.9	595.4	600.1	598.5	10- 20	174.7	236.1	13.1,13.1
30	534.1	533.2	538.5	530.0	529.1	534.7	544.8	538.4	20- 30	261.6	497.7	27.6,27.6
40	445.8	455.5	469.9	451.3	440.6	458.6	478.5	463.1	30- 40	311.2	808.9	44.8,44.8
50	345.0	367.6	388.3	363.5	339.6	372.8	398.1	376.6	40- 50	319.0	1128	62.5,62.5
60	240.2	273.2	293.1	269.0	235.4	278.7	303.1	283.3	50- 60	286.5	1414	78.4,78.4
70	138.6	177.6	193.0	174.1	134.4	183.7	202.2	187.5	60- 70	220.9	1635	90.6,90.6
80	47.93	90.43	102.1	87.66	45.26	95.61	110.3	98.42	70- 80	136.5	1772	98.2,98.2
90	0.5045	0	0	0	0.4152	0	0	0	80- 90	32.78	1805	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 970.02 lm

%lum = 53.8%

%lamp = 53.8%

Conical surface Flux(120deg): 1414.4 lm

%lum = 78.4%


%lamp = 78.4%

H(β) Range:-90 - 90DEG
 H(β) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CL
 Test Date:23 December 2019

V(B) Range:-80 - 80DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:6.010m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	1644	0
80	2760	5879
75	3514	5700
70	4052	5642
65	4461	5751
60	4803	5862
55	5103	5940
50	5367	6040
45	5607	6068


H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:23 December 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.04	.99	.96	1.02	.98	.94	.97	.94	.91	.93	.91	.88	.90	.88	.86	.84
2.0	.90	.83	.78	.88	.82	.77	.85	.80	.75	.82	.77	.73	.79	.75	.72	.69
3.0	.79	.71	.64	.78	.70	.64	.75	.68	.63	.72	.66	.62	.69	.65	.61	.58
4.0	.70	.61	.55	.69	.61	.54	.66	.59	.53	.64	.58	.53	.62	.56	.52	.50
5.0	.63	.54	.47	.62	.53	.47	.59	.52	.46	.57	.51	.46	.56	.50	.45	.43
6.0	.56	.47	.41	.56	.47	.41	.54	.46	.40	.52	.45	.40	.50	.44	.40	.38
7.0	.51	.42	.36	.50	.42	.36	.49	.41	.36	.47	.41	.36	.46	.40	.35	.33
8.0	.47	.38	.32	.46	.38	.32	.45	.37	.32	.43	.37	.32	.42	.36	.32	.30
9.0	.43	.35	.29	.42	.34	.29	.41	.34	.29	.40	.33	.29	.39	.33	.29	.27
10.0	.40	.32	.26	.39	.31	.26	.38	.31	.26	.37	.31	.26	.36	.30	.26	.24



H(β) Range:-90 - 90DEG
 H(β) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CL
 Test Date:23 December 2019

V(B) Range:-80 - 80DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:6.010m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.311	.177	.056	.304	.173	.055	.291	.167	.053	.278	.161	.052	.267	.155	.050		
2.0	.293	.160	.049	.286	.158	.049	.275	.153	.047	.264	.148	.046	.254	.144	.045		
3.0	.271	.144	.043	.265	.142	.043	.255	.138	.042	.245	.134	.041	.236	.131	.040		
4.0	.249	.130	.038	.245	.128	.038	.235	.125	.037	.227	.122	.037	.219	.119	.036		
5.0	.230	.117	.034	.226	.116	.034	.218	.113	.033	.210	.111	.033	.203	.109	.033		
6.0	.214	.107	.031	.210	.106	.030	.202	.104	.030	.196	.102	.030	.189	.100	.030		
7.0	.199	.098	.028	.195	.097	.028	.189	.095	.027	.183	.094	.027	.177	.092	.027		
8.0	.186	.091	.025	.182	.090	.025	.177	.088	.025	.171	.087	.025	.166	.085	.025		
9.0	.174	.084	.023	.171	.083	.023	.166	.082	.023	.161	.081	.023	.156	.079	.023		
10.0	.163	.078	.022	.161	.078	.022	.156	.077	.022	.152	.075	.021	.148	.074	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.180	.156	.134	.154	.134	.116	.106	.092	.080	.061	.053	.046	.019	.017	.015	
2.0	.172	.132	.098	.148	.114	.085	.101	.079	.059	.058	.046	.035	.019	.015	.011	
3.0	.165	.114	.074	.141	.099	.064	.097	.069	.045	.056	.040	.027	.018	.013	.009	
4.0	.157	.101	.058	.135	.087	.051	.093	.061	.036	.054	.036	.021	.017	.012	.007	
5.0	.149	.091	.047	.128	.078	.041	.088	.055	.029	.051	.032	.017	.017	.010	.006	
6.0	.142	.082	.039	.122	.071	.034	.084	.050	.024	.049	.029	.014	.016	.010	.005	
7.0	.135	.075	.033	.116	.065	.029	.080	.046	.021	.047	.027	.012	.015	.009	.004	
8.0	.129	.070	.029	.111	.060	.025	.077	.042	.018	.045	.025	.011	.014	.008	.004	
9.0	.123	.065	.025	.106	.056	.022	.073	.039	.016	.043	.023	.009	.014	.008	.003	
10.0	.117	.060	.022	.101	.052	.020	.070	.037	.014	.041	.022	.008	.013	.007	.003	

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:23 December 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm											
NAME: Linear					TYPE:Linear			WEIGHT:			
SPEC.:20W					DIM.:			SERIAL No.:N/A			
MFR.: NJZ Lighting Technology Co.,Ltd					SUR.:N/A			Shielding Angle:N/A			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	16.3	17.8	16.5	18.0	18.2	17.1	18.6	17.4	18.8	19.0
	3H	17.6	19.0	17.9	19.2	19.4	18.8	20.2	19.1	20.4	20.7
	4H	18.0	19.4	18.3	19.6	19.9	19.6	20.9	19.9	21.2	21.4
	6H	18.3	19.6	18.6	19.8	20.1	20.2	21.5	20.6	21.8	22.1
	8H	18.4	19.6	18.7	19.9	20.2	20.4	21.6	20.7	21.9	22.2
	12H	18.4	19.5	18.7	19.8	20.1	20.4	21.6	20.7	21.8	22.2
4H	2H	17.0	18.3	17.3	18.6	18.9	17.7	19.0	18.0	19.2	19.5
	3H	18.5	19.7	18.9	20.0	20.3	19.6	20.8	19.9	21.1	21.4
	4H	19.1	20.2	19.5	20.5	20.9	20.5	21.6	20.9	21.9	22.2
	6H	19.6	20.5	20.0	20.9	21.2	21.4	22.3	21.8	22.7	23.0
	8H	19.7	20.6	20.1	20.9	21.3	21.6	22.4	22.0	22.8	23.2
	12H	19.7	20.5	20.1	20.9	21.3	21.6	22.4	22.0	22.8	23.2
8H	4H	19.6	20.5	20.0	20.9	21.2	20.8	21.7	21.2	22.0	22.4
	6H	20.2	21.0	20.7	21.4	21.8	21.8	22.6	22.3	23.0	23.4
	8H	20.4	21.1	20.9	21.5	22.0	22.1	22.8	22.6	23.2	23.7
	12H	20.6	21.1	21.0	21.6	22.0	22.1	22.7	22.6	23.2	23.6
12H	4H	19.7	20.5	20.1	20.9	21.3	20.8	21.6	21.2	22.0	22.4
	6H	20.4	21.0	20.8	21.5	21.9	21.9	22.6	22.4	23.0	23.4
	8H	20.7	21.2	21.2	21.7	22.2	22.2	22.8	22.7	23.2	23.7
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.1 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 1805 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 2.1$)

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CL
 Test Date:23 December 2019

$V(B)$ Range:-80 - 80DEG
 $V(B)$ Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:6.010m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	58	46	39	57	46	39	56	45	39	32
0.80	68	56	49	67	56	49	65	55	48	41
1.00	76	65	58	75	64	57	73	66	57	50
1.25	83	73	65	82	72	65	79	70	64	57
1.50	88	78	71	86	77	71	83	75	70	62
2.00	95	86	80	93	85	79	90	83	78	70
2.50	99	91	85	97	90	84	93	87	82	74
3.00	102	95	90	100	94	89	96	91	86	78
4.00	106	100	96	104	99	94	100	95	92	83
5.00	109	104	100	106	102	98	102	98	95	86
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CL
 Test Date:23 December 2019

$V(B)$ Range:-80 - 80DEG
 $V(B)$ Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:6.010m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A




H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:23 December 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

AAI Figure

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Flux out:1189 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:23 December 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:23 December 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A


AvgL	cd/m2
L_0~180 (65) av	4410
L_0~180 (75) av	3446
L_0~180 (85) av	1553
L_90~270 (65) av	5864
L_90~270 (75) av	5869
L_90~270 (85) av	0
L_45 (65) av	5388
L_45 (75) av	5209
L_45 (85) av	3265

Standard: GB/T 29293-2012

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:23 December 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

Planar Illuminance Curve



H(β) Range:-90 - 90DEG
 H(β) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CL
 Test Date:23 December 2019

V(B) Range:-80 - 80DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:6.010m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--1

UNIT: cd

[illegible]

```
H( $\beta$ ) Range:-90 - 90DEG
H( $\beta$ ) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:23 December 2019
```

```
V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:
```

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--2

UNIT: cd

[illegible]

```
H( $\beta$ ) Range:-90 - 90DEG
H( $\beta$ ) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:23 December 2019
```

```
V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:
```

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--3

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:23 December 2019

```
V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:
```

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:219.74V I:0.0997A P:20.397W PF:0.9311 Freq:49.99Hz Lamp Flux:1804.51x1 lm		
NAME: Linear	TYPE:Linear	WEIGHT:
SPEC.:20W	DIM.:	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--4

UNIT: cd

[illegible]

```
H( $\beta$ ) Range:-90 - 90DEG
H( $\beta$ ) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:23 December 2019
```

```
V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:
```