


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

DATA OF LAMP		PHOTOMETRIC DATA Eff: 128.46 lm/W			
MODEL NJZ-FEL-I-6-V01-RN-60		Imax(cd)	619.1	S/MH(C0/180)	0.92
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	0.99
RATED VOLTAGE(V)		TOTAL FLUX(lm)	765.61	η UP,DN(C0-180)	0.0,46.7
NOMINAL FLUX(lm)	765.61	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,53.3
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.00
TEST VOLTAGE(V)		η down(%)	100.0	CIBSE SHR MAX	1.00

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	587.0	561.6	561.0	556.5	576.5	584.8	600.6	590.9	0- 10	56.45	56.45	7.37,7.37
20	491.0	456.2	448.9	448.8	480.9	498.1	521.7	508.2	10- 20	149.5	205.9	26.9,26.9
30	335.2	309.4	305.6	308.6	334.3	358.2	372.5	364.3	20- 30	187.7	393.6	51.4,51.4
40	188.9	171.5	166.0	172.8	193.1	209.9	209.8	213.5	30- 40	162.5	556.1	72.6,72.6
50	93.03	81.53	80.75	84.36	94.43	108.3	105.9	110.0	40- 50	107.2	663.3	86.6,86.6
60	42.42	37.50	38.02	40.78	44.52	52.19	48.35	56.16	50- 60	60.81	724.1	94.6,94.6
70	18.58	16.41	14.46	17.87	19.36	21.78	13.54	23.18	60- 70	30.13	754.2	98.5,98.5
80	4.513	3.523	0.5123	3.669	4.948	3.638	0.3813	3.484	70- 80	10.54	764.8	99.9,99.9
90	0.0819	0	0	0	0.0526	0	0	0	80- 90	0.8378	765.6	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 616.47 lm

%lum = 80.5%

%lamp = 80.5%

Conical surface Flux(120deg): 724.11 lm

%lum = 94.6%


%lamp = 94.6%

H(β) Range:-90 - 90DEG
 H(β) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CL
 Test Date:18 June 2019

V(B) Range:-80 - 80DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:6.010m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	87	0
80	260	30
75	412	289
70	543	423
65	660	621
60	848	760
55	1104	1035
50	1447	1256
45	1905	1745


H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.09	1.06	1.03	1.07	1.04	1.01	1.02	1.00	.98	.99	.97	.95	.95	.94	.92	.91
2.0	.99	.94	.90	.97	.93	.89	.94	.90	.87	.91	.88	.85	.88	.85	.83	.81
3.0	.90	.84	.79	.89	.83	.79	.86	.81	.77	.83	.79	.76	.81	.78	.75	.73
4.0	.83	.76	.71	.81	.75	.70	.79	.74	.69	.77	.72	.69	.75	.71	.68	.66
5.0	.76	.69	.64	.75	.68	.63	.73	.67	.63	.71	.66	.62	.70	.65	.62	.60
6.0	.70	.63	.58	.69	.62	.58	.68	.62	.57	.66	.61	.57	.65	.60	.56	.55
7.0	.65	.58	.53	.64	.57	.53	.63	.57	.52	.62	.56	.52	.60	.55	.52	.50
8.0	.60	.53	.49	.60	.53	.48	.59	.53	.48	.57	.52	.48	.56	.51	.48	.46
9.0	.56	.50	.45	.56	.49	.45	.55	.49	.45	.54	.48	.44	.53	.48	.44	.43
10.0	.53	.46	.42	.52	.46	.42	.51	.46	.41	.51	.45	.41	.50	.45	.41	.40



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.217	.123	.039	.210	.120	.038	.197	.113	.036	.186	.107	.034	.175	.101	.033		
2.0	.211	.115	.035	.205	.113	.035	.194	.108	.033	.184	.103	.032	.174	.099	.031		
3.0	.201	.107	.032	.196	.105	.032	.186	.101	.031	.177	.097	.030	.169	.094	.029		
4.0	.190	.099	.029	.185	.097	.029	.177	.094	.028	.169	.091	.027	.162	.088	.027		
5.0	.180	.091	.026	.176	.090	.026	.168	.088	.026	.161	.085	.025	.155	.083	.025		
6.0	.170	.085	.024	.166	.084	.024	.160	.082	.024	.154	.080	.023	.148	.078	.023		
7.0	.161	.079	.023	.158	.079	.022	.152	.077	.022	.147	.075	.022	.141	.073	.022		
8.0	.152	.075	.021	.150	.074	.021	.145	.072	.021	.140	.071	.020	.135	.069	.020		
9.0	.145	.070	.020	.142	.069	.019	.138	.068	.019	.133	.067	.019	.129	.066	.019		
10.0	.138	.066	.018	.136	.066	.018	.131	.064	.018	.127	.063	.018	.124	.062	.018		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.174	.157	.142	.149	.135	.122	.102	.093	.084	.059	.054	.049	.019	.017	.016	
2.0	.161	.132	.108	.138	.114	.093	.095	.079	.065	.055	.046	.038	.018	.015	.012	
3.0	.151	.114	.084	.130	.098	.073	.089	.068	.051	.051	.040	.030	.017	.013	.010	
4.0	.142	.100	.067	.122	.086	.058	.084	.060	.041	.049	.035	.024	.016	.011	.008	
5.0	.134	.089	.055	.115	.077	.048	.080	.054	.034	.046	.031	.020	.015	.010	.007	
6.0	.127	.080	.045	.110	.069	.040	.076	.048	.028	.044	.028	.017	.014	.009	.005	
7.0	.121	.072	.038	.104	.063	.033	.072	.044	.024	.042	.026	.014	.014	.008	.005	
8.0	.115	.066	.033	.099	.058	.029	.069	.040	.020	.040	.024	.012	.013	.008	.004	
9.0	.110	.061	.029	.095	.053	.025	.066	.037	.018	.038	.022	.011	.012	.007	.004	
10.0	.105	.057	.025	.091	.050	.022	.063	.035	.016	.037	.021	.009	.012	.007	.003	

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm										
NAME: LED Explosion-proof Flood Light					TYPE:Floodlight			WEIGHT:N/A		
SPEC.:3000K					DIM.: N/A			SERIAL No.:N/A		
MFR.: NJZ Lighting Technology Co.,Ltd					SUR.:N/A			Shielding Angle:N/A		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	12.3	13.4	12.5	13.6	13.8	12.0	13.2	12.3	13.4	13.6
3H	12.5	13.6	12.8	13.8	14.0	12.3	13.4	12.6	13.6	13.8
4H	12.6	13.6	12.9	13.9	14.1	12.3	13.4	12.6	13.6	13.8
6H	12.6	13.6	12.9	13.8	14.1	12.3	13.2	12.6	13.5	13.7
8H	12.6	13.5	12.9	13.8	14.0	12.2	13.1	12.5	13.4	13.7
12H	12.5	13.4	12.9	13.7	14.0	12.2	13.1	12.5	13.3	13.6
4H 2H	12.3	13.3	12.6	13.6	13.8	12.1	13.1	12.4	13.4	13.6
3H	12.7	13.6	13.0	13.9	14.1	12.5	13.4	12.8	13.7	14.0
4H	12.8	13.6	13.2	13.9	14.2	12.6	13.4	12.9	13.7	14.0
6H	12.9	13.6	13.2	13.9	14.3	12.5	13.2	12.9	13.6	13.9
8H	12.8	13.5	13.2	13.8	14.2	12.5	13.1	12.9	13.5	13.9
12H	12.8	13.4	13.2	13.8	14.2	12.4	13.0	12.9	13.4	13.8
8H 4H	12.8	13.4	13.2	13.8	14.2	12.6	13.2	13.0	13.6	13.9
6H	12.9	13.4	13.3	13.8	14.2	12.5	13.0	12.9	13.4	13.9
8H	12.9	13.3	13.3	13.7	14.2	12.5	12.9	12.9	13.4	13.8
12H	12.8	13.2	13.3	13.7	14.1	12.4	12.8	12.9	13.3	13.7
12H 4H	12.8	13.3	13.2	13.7	14.1	12.5	13.1	12.9	13.5	13.9
6H	12.8	13.3	13.3	13.7	14.2	12.5	12.9	12.9	13.4	13.8
8H	12.8	13.2	13.3	13.7	14.1	12.4	12.8	12.9	13.3	13.7
Variations with the observer position at spacings:										
S = 1.0H	+ 1.1 / - 1.4					+ 1.0 / - 1.5				
1.5H	+ 1.5 / - 1.3					+ 1.3 / - 1.2				
2.0H	+ 2.5 / - 2.1					+ 2.2 / - 2.0				

CIE Pub.117, 765.6 lm Total Lamp Luminous Flux Correct (8log(F/F0) = -0.9)

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	74	66	60	74	65	60	73	65	60	55
0.80	83	75	70	83	75	70	81	74	69	64
1.00	90	82	77	89	82	77	87	82	76	71
1.25	96	88	84	94	88	83	92	87	82	77
1.50	99	93	88	98	92	88	95	90	87	81
2.00	104	98	94	102	97	93	99	95	92	85
2.50	106	101	97	105	100	96	101	97	94	88
3.00	109	104	100	107	103	99	103	100	97	90
4.00	111	107	104	109	106	103	105	103	100	93
5.00	113	110	107	111	108	105	106	104	102	94
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHR NOM = 1.25		

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CL
 Test Date:18 June 2019

$V(B)$ Range:-80 - 80DEG
 $V(B)$ Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:6.010m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A




H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

AAI Figure

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Flux out:429.8 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A


AvgL	cd/m2
L_0~180 (65) av	680
L_0~180 (75) av	426
L_0~180 (85) av	96
L_90~270 (65) av	677
L_90~270 (75) av	279
L_90~270 (85) av	0
L_45 (65) av	754
L_45 (75) av	378
L_45 (85) av	15

Standard: GB/T 29293-2012

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

Planar Illuminance Curve



H(β) Range:-90 - 90DEG
 H(β) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CL
 Test Date:18 June 2019

V(B) Range:-80 - 80DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:6.010m [K=1.0000]
 Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--1

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--2

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--3

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

```
V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:
```

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:34.640V I:0.1720A P:5.9600W PF:0.0000 Freq:0Hz Lamp Flux:765.61x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:3000K	DIM.: N/A	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--4

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:18 June 2019

```
V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:
```